

nilnadumedicalsystem.com

Spontaneous BiLevel









Dimensions (H x W x L) 10.8 × 16.5 × 17.8 cm

Weight 1.18 kg

BiLevel Pressure Range

Operating

 5° C to 40° C; $0\,\%$ to $95\,\%$ R.H. non-condensing

Atmospheric Conditions Sea level to 2,700 m

Storage & Transportation

- 40° C to + 70° C; 0% to 95% R.H. non-condensing

Sound Level < 26 dB(A)

Maximum Power Consumption 65 W from AC power source

(PAP device only)

Electrical Requirements

100 - 240 VAC, 50/60 Hz



DeVilbiss Healthcare Ltd. Unit 3, Bloomfield Park, Bloomfield Road Tipton, West Midlands DY4 9AP United Kingdom

Phone + 44 (0) 121 521 3140

Fax + 44 (0) 121 521 3141

www.devilbisshc.com

enquiries@devilbisshc.com

The SleepCube BiLevel S is a variation on traditional CPAP. Instead of providing air at a constant pressure all night, the machine "senses" if you are breathing in or out and varies its level of pressure accordingly.

On inspiration a higher pressure is needed to prevent apnoeas, hypoapnoeas or snoring. On expiration a lower pressure is adopted to ensure patient comfort with less resistance. A BiLevel S is particularly useful for those patients who require high pressures.

By connecting the SmartLink compliance module to the SleepCube BiLevel S overnight patient compliance data is recorded. This data is transferred to the SmartLink Software by Smart Card. Overnight oximetry can be added to the SmartLink if required. As with our Auto

and Standard SleepCubes, the BiLevel S contains SmartCode, our unique patient adherence system. SmartCode allows patient average usage data to be reported remotely in a very simple and easy to use manner.

Features and benefits

- Pressure range of 3 25 cm H₂O in both BiLevel and CPAP mode
- Pressure difference between the IPAP pressure setting and EPAP pressure setting can be up to 22 cm H₂O
- Delay mode is adjustable in 5 minute increments up to 45 minutes
- Maintains the same triggering sensitivity with a high leak rate (up to 80 l/min.) as at a normal mask leak rate
- A "Soft Start" feature: this permits the patient to acclimatize to the pressure after the unit is powered on



The simple LED push button display, makes the SleepCube easy to use, even in the dark



Back of the SleepCube – showing filter and patient tubing outlet



SleepCube with integrated heated humidifier



 ${\it SleepCube\ BiLevel\ S\ with\ SmartLink\ unit\ attached}$

Distributor: